



d(mm)	Part No.	L(mm)	Grip Range (mm)		Drill Size (mm)	D(mm)	dm(mm)	P(mm)	Tracción Tensile (N)	Cizalla Shear (N)
			Min	Max		Max	Max	Min		
d=2,4	R0092406	6	2,0	4,0	2,5	5,0	1,37	26	500	300
	R0092408	8	4,0	6,0						
	R0092410	10	6,0	8,0						



Este plano es propiedad de Remaches Tudela S.L. todos los derechos reservados/ This drawing is the property of Remaches Tudela S.L. all rights reserved									
DIBUJADO / DRAWN BY FECHA / DATE		J.SANZ 15/11/2021		DENOMINACIÓN DESCRIPTION		REMACHE CABEZA AVELLANADA ESTÁNDAR/ COUNTERSUNK HEAD STANDARD RIVET		ESPECIFICACIONES GENERALES GENERAL SPECIFICATIONS	
REVISIÓN / REVISION FECHA / DATE		Rev. 0 15/11/2021		CUERPO / BODY		CLAVO / MANDREL		TOLERANCIAS Según plano/ TOLERANCES According drawing	
REMACHES TUDELA		MATERIAL		ALUMINIO 3,5% MG ALUMINUM 3,5% MG		ACERO STEEL		UNIDADES mm	
		ACABADO FINISHED		ABRILLANTADO BRIGHTNESS		CINCADO ZINC PLATED			
REFERENCIA REFERENCE				R00924				A4	